

High Flow Multiple Cartridge Filter Housing

Trusted Filtration Solutions

Specifications

Material	SS304, 316L SS, Carbon Steel
Finishing	Mirror polished, Sand blast
Inlet/Outlet	4" to 12" Flange
Vent	1/4" NPT(F), 3/4" Flange
Max. Pressure	150 psi
Design Temperature	50 ~ 200 degree celcius



Typical Applications

- Pre-filtration of RO or other distillation system
- Condensate water filtration, hot water recovery in power generation
- API, solvents and water filtration for Bio Pharm
- Filtration of bottled water, high fructose, edible oil, soft drinks, milk
- Coating, Paints, petrochemical, refineries
- Microelectronics, film, fibre, resin

Model	Cartridges	Inlet/ Outlet	M ³ /Hour
KHFH-20	1 x 20"	4"	20
KHFH-40	1 x 40"	4"	40
KHFH-60	1 x 60"	4"	60
KHFH-120	2 x 60"	6"	120
KHFH-180	3 x 60"	6"	180
KHFH-240	4 x 60"	6"	240
KHFH-300	5 x 60"	6"	300
KHFH-360	6 x 60"	6"	360
KHFH-420	7 x 60"	6"	420
KHFH-480	8 x 60"	6"	480
KHFH-540	9 x 60"	6"	540
KHFH-600	10 x 60"	6"	600
KHFH-660	11 x 60"	6"	660
KHFH-720	12 x 60"	6"	720
KHFH-780	13 x 60"	8"	780
KHFH-840	14 x 60"	8"	840
KHFH-900	15 x 60"	8"	900
KHFH-960	16 x 60"	10"	960
KHFH-1020	17 x 60"	10"	1020
KHFH-1080	18 x 60"	10"	1080
KHFH-1140	19 x 60"	10"	1140
KHFH-1200	20 x 60"	10"	1200
KHFH-1260	21 x 60"	12"	1260
KHFH-1320	22 x 60"	12"	1320
KHFH-1380	23 x 60"	12"	1380
KHFH-1440	24 x 60"	12"	1440

Contact

KETCOTEC (M) SDN. BHD.
6, Jalan 3/5,
Bandar Baru Selayang,
68100 Batu Caves Selangor,
Malaysia

sales@filter.com.my

+603 - 61363211

+6012 - 3013211



Scan me