

STAINLESS STEEL PLEATED CARTRIDGE FILTER

Features

- Excellent chemical compatibility
- Good permeability
- Low clean pressure drop
- Large filtration surface
- Stable filter rating

Specifications

Material	SUS304, SUS316L
Filter media	Stainless steel wire mesh
Standard Connection	• Double open end • Single open end with 222 / flat • Single open end with 226 / flat
Max. Temperature	480°C
Size	Length : 10", 20", 30", 40"
Max. dP	5 barg



Applications

- Polymers
- Plastics
- Pharmaceutical
- F&B

Filtration efficiency

1, 3, 5, 10, 50, 100 µm

Ordering Guide

KSSPC	4	4	05	S	E
	Material	Length	Removal Efficiency (micron)	Ending Cap	Gasket
	4: SS 304 6: SS 316L	1: 10" 2: 20" 3: 30" 4: 40"	01 = 1µm 03 = 3µm 05 = 5µm 10 = 10µm 50 = 50µm 100 = 100µm	blank = DOE 2 = 222/flat 3 = 222/fin 6 = 226/flat 7 = 226/fin	E : EPDM N : Buna N S : Silicone V : Viton

Contact

 KETCOTEC (M) SDN. BHD.
6, Jalan 3/5,
Bandar Baru Selayang,
68100 Batu Caves Selangor,
Malaysia

 sales@filter.com.my

 KETCOTEC (M) Sdn. Bhd

 +603 - 61363211

 +6012 - 3013211

